

DISCRIPTION

VALVE SERVE VALVE CLEANER: P/N AVS – C500 is not a Sealant, it is a combination of solvent and semi synthetic lubricant oils. Formulated to be injected directly in to the seat sealant system to **Clean Seal Faces and Sealant Passage**. Cycle of the valve to insure complete coverage to allow the valve cleaner to soften old sealant and remove residual build up from seal points. Valve with sever or persistent leakage may require more wait time. The best results are achieved by displacing the valve cleaner with equal quantities of lubricant/sealant after cleaning.

- Recommended for use in Ball, Gate or Plug Valve and Orifice Fitting.
- For use at refineries, wellheads, pumps or compressor station and in gas distribution system

AVS-C500

Non-Flammable, Non-Carcinogenic, Non-Ozone Depleting

Packing Available

18. Ltr/ Pail

VALVE CLEANER

Product Specifications: AVS – C500

color	: <i>Black Paste</i>
Base Oil	: <i>Semi-Synthetic</i>
Drop Point	: <i>+ 235 °C or 455 °F</i>
Texture	: <i>Thin Paste</i>
Pressure	: <i>15000PSI</i>
ASTM Penetration	: <i>270-330</i>
Compatibility	: <i>Dispersant</i>
Solvent Resistance	: <i>N/A</i>
Special Additives	: <i>Molybdenum Disulfide</i>
Composition	: <i>Semi-Liquid</i>
Temperature Range	<i>-40°C to +204°C</i> <i>-40°F to +400°F</i>

Valve Serve

Advanced Valve Services Co.Ltd

Ph.: +966 13- 887 6868 Fax: +966 13- 887 8821

Email: Info@valveserve.sa website: www.valveserve.sa