

DISCRIPTION

GAS LUBRICANT P/N: AVS – HT750 is a proprietary blend of synthetic ingredients that when combined, exceed the rating of the component.as a result AVS-HT750 Lubricant/Sealant withstands temperature up to +398°C or +750°F with minimal thermal decomposition

AVS-HT750

GAS LUBRICANT (AVS-HT750) provides an insoluble film of synthetic lubricant to protect valve seal faces and reduce torque requirements. AVS – HT750 is non-melting and insoluble in water, steam and related by products. The viscosity of AVS-HT750 allows the ease of application using a brush, grease pump or automatic injection equipment.

In cases of extreme valve leakage where regular sealants do not achieve desired results, AVS-HT750 offers a full range of specialty sealants to achieve a reliable temporary seal.

Available Packing
18. Ltr / pail

GAS LUBRICANT

Product Specifications: AVS – HT750

Color	:	Black
Base Oil	:	Synthetic
Drop Point	:	+327°C or +621°F
Texture	:	Tacky
NLGI Grade	:	1
ASTM Penetration	:	260-340
Compatibility	:	Excellent
Solvent Resistance	:	Excellent
Special Additives	:	Moly
Particle Size	:	< 4 Micron
Composition	:	Semi-Liquid
Temperature Range	:	-30°C to +400°C -21°F to +750°F

Valve Serve

Advanced Valve Services Co.Ltd

Ph.: +966 13- 887 6868 Fax: +966 13- 887 8821

Email: Info@valveserve.sa website: www.valveserve.sa