

## **DESCRIPTION**

**VALVE SERVE SEALANT GREASE: AVS-337** Provides an effective film of lubricant to protect seal faces and reduces torque requirements. Incorporated with microscopic particles of PTFE, total lube will seal minor scratches to sealing surfaces and shallow corrosion pits. Seals scratches up to 0.010" and nicks and cuts on soft seats.

Designed specifically as an all-purpose seat lubricant/sealant to extend the maintenance interval in severe service and critical service valves.

AVS-337

VALVE SERVE SEALANT is insoluble in water, oil, natural gas and related by-products.

Recommended for use in ball valves, gate valves and plug valves and also for orifice fittings.

Used at refineries, wellheads, pumps and compressor stations and in gas distribution system.

Available Packing  
18. Ltr / Pail

## **Sealant Grease**

### **Product Specifications: AVS – 337**

<b>Color</b>	:	White
<b>Base Oil</b>	:	Synthetic
<b>Drop Point</b>	:	None
<b>Texture</b>	:	tacky
<b>Pressure</b>	:	15000PSI
<b>ASTM Penetration</b>	:	170-250
<b>Compatibility</b>	:	Excellent
<b>Solvent Resistance</b>	:	Excellent
<b>Special Additives</b>	:	PTFE
<b>Composition</b>	:	Viscose
<b>Particle Size</b>	:	Micronized
<b>Temperature Range</b>	:	-29°C to +232°C -20°F to +450°F

**Valve Serve**

**Advanced Valve Services Co.Ltd**

Ph.: +966 13- 887 6868 Fax: +966 13- 887 8821

Email: [Info@valveserve.sa](mailto:Info@valveserve.sa) website: [www.valveserve.sa](http://www.valveserve.sa)