

## **DISCRIPTION**

### VALVE SERVE HIGH PRESURE GREASE

**AVS – 88** provides an insoluble film of lubricant to protect critical seal faces and reduce torque requirements. Extend valve service life by injecting **VAVLE SERVE HIGH PRESURE GREASE** immediately after the hydrostatic test at the valve factory or repair facility. Thus will purge all the test water from the seat pockets where corrosion commonly occurs.

Protects against damage from pipeline contaminates, such as dirt, sand, line scale and welding slag at start-up. Insoluble in water, crude oil, natural gas, condensate and related by-products

**AVS-88**

**Recommended for use in new valves, wellhead valves, at refineries, pump and compress stations and in gas.**

Packing Available  
18. Ltr / Pail

## **HIGH PREASURE GREASE**

### **Product Specifications: AVS - 88**

<b>color</b>	: YELLOW
<b>Base Oil</b>	: <i>Synthetic</i>
<b>Drop Point</b>	: <i>None</i>
<b>Texture</b>	: <i>Tacky</i>
<b>Pressure</b>	: <i>15000PSI</i>
<b>ASTM Penetration</b>	: <i>220-280</i>
<b>Compatibility</b>	: <i>Excellent</i>
<b>Solvent Resistance</b>	: <i>Excellent</i>
<b>Special Additives</b>	: <i>None</i>
<b>Particle Size</b>	: <i>N/A</i>
<b>Composition</b>	: <i>Semi-Liquid</i>
<b>Temperature Range</b>	-40°C to +149°C -40°F to +300°F

**Valve Serve**

**Advanced Valve Services Co.Ltd**

Ph.: +966 13- 887 6868 Fax: +966 13- 887 8821

Email: [Info@valveserve.sa](mailto:Info@valveserve.sa) website: [www.valveserve.sa](http://www.valveserve.sa)